Safety Data Sheet

CLP: According to 2015/830/EU Vers

Version 2 Revised: 01/08/2022

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

Product Name: URINAL SCREEN Ocean FRAGRANCE 4% IN PVC

Code Number: 104748

Alternative Name:

REACH Reg No: Not Registered

1.2 Relevant identified uses of the substance or mixture and uses advised against

Concentrated fragrance material for manufacturing purposes only.

1.3 Details of the supplier of the safety data sheet

Robert Scott & Sons Ltd Oak View Mills Greenfield Oldham Lancashire OL3 7HG

Tel: +44 (0) 1457 819 400 Email: <u>sales@robert-scott.co.uk</u>

Section 2. Hazard Identification

2.1 Classification of the substance or mixture

EH C3 Aquatic Hazard, Chronic, Category 3

2.2 CLP Label elements

CLP classification according to Regulation (EC) No 1272/2008

Hazard Statements

H412 Harmful to aquatic life with long lasting effects

Precautionary Statements

P273 Avoid release to the environment.

P501 Dispose of contents and container in accordance with local regulation.

2.3 Other Hazards

Contains alpha-iso-Methylionone, Citral, Geraniol, Hexyl Cinnamal, Limonene and Linalool which may produce an allergic reaction.

Section 3. Composition / information on ingredients

The information contained herein is true and accurate to the best of our knowledge. All information is valid until revisions are issued. However, the accuracy of this information cannot be guaranteed by the company as the data has been obtained from different sources. We will not, therefore, accept liability for misuse of this data resulting in damage or loss.

3.1 Mixtures

Complex mixture of fragrance ingredients

Hazardous components

ID Numbers	Chemical Name, Classification and Hazards	Conc (%)
CAS 5989-27-5 EINECS 227-813-5 REACH	d-Limonene (p-Mentha-1,8-diene) FL 3;SCI 2;SS 1B;AH 1;EH A1,C1 H226,H304,H315,H317,H400,H410	>=0.1%,<1%
CAS 54464-57-2 EINECS 259-174-3 REACH	Iso E super (Octahydro-2,3,8,8-tetramethyl-2-acetonaphthone) SCI 2;SS 1;EH C2 H315,H317,H411	>=0.1%,<1%
CAS 110-41-8 EINECS 203-765-0 REACH	Aldehyde C-12 MNA (2-Methyl undecanal) SCI 2;SS 1B;EH A1,C1 H315,H317,H400,H410	>=0.1%,<1%

Refer to section 16 for the wording of listed classification and hazard statement codes

Section 4. First Aid measures

Take phrases in section 2 into account

4.1 Description of First Aid

Measures after inhalation

Treat as for choking, obtain immediate medical attention. Mouth to mouth resuscitation should be used only in extreme cases as it may force pellets further into a respirator.

In the unlikely event of inhalation of hot melt, treat as for choking but expect severe burns to respiratory tract. Obtain immediate medical attention.

After skin contact

Seek medical advice if irritation persists after washing thoroughly with soap and water or there is any sign of tissue damage.

Section 5. Fire-fighting measures

5.1 Suitable extinguishing materials

Water, water mist, carbon dioxide foam, earth, sand and dry powder

5.2 Unsuitable extinguishing materials

None

5.3 Major Incidents

For major fires and those in confined areas self contained breathing apparatus and acid resistant protective clothing should be used. Shower with plenty of water to remove acid fumes. Soak contaminated clothing in 1% sodium bicarbonate solution before re-laundering for reuse.

Section 6: Accidental release measures

Refer to information in sections 7,8 and 13

The information contained herein is true and accurate to the best of our knowledge. All information is valid until revisions are issued. However, the accuracy of this information cannot be guaranteed by the company as the data has been obtained from different sources. We will not, therefore, accept liability for misuse of this data resulting in damage or loss.

Section 7. Handling and storage

7.1 Storage

Store in dry adequately ventilated areas at room temperature. Avoid sources of heat and ignition. Store away from food, drink, and animal feeds. Damp storage may affect the strength of the paper packaging.

7.2 Fire and Explosion

PVC is not readily ignitable but will burn releasing toxic fumes. Avoid source of ignition. Usually it is more likely that fire will be initiated by ignition of packaging (paper/polythene bags, wooden pallets or cardboard boxes) rather than the Compound itself.

Section 8. Exposure controls / personal protection

8.1 Individual protection measures

Refer to Section 5 for specific fire/chemical personal protective equipment advice. Always wash routinely before breaks, meals and at the end of the work period.

Section 9: Physical and chemical properties

9.1 Melting Point

Softens at about 130 degC

9.2 Decomposition Temperature

Decomposition depends on time and temperature but will initiate at about 130 degC where it will take several hours or days. At 200 degC it will increase rapidly, taking only a few minutes. Decomposition releases hydrogen chloride fumes.

Section 10: Stability and reactivity

10.1 Stability

If stored and used in accordance with standard practice this product is unlikely to cause harmful effects.

10.2 Conditions to Avoid

High temperatures. Will melt to a coagulated mass above 100degC; decompose at temperatures over 130degC. Also avoid sources of ignition.

Section 11. Toxicological information

11.1 Information on Toxicological effects Acute Toxicity

ALLYL CYCLOHEXYL PROPIONATE (CAS: 2705-87-5)

Oral route: LD50 = 820 mg/kg Dermal route: LD50 = 1600 mg/kg Inhalation route: Data not available

Section 12. Ecological information

12.1 Break Down

Finished articles, is considered ecologically benign. PVC compound is not easily broken down by either micro-organisms or weathering.

The information contained herein is true and accurate to the best of our knowledge. All information is valid until revisions are issued. However, the accuracy of this information cannot be guaranteed by the company as the data has been obtained from different sources. We will not, therefore, accept liability for misuse of this data resulting in damage or loss.

12.2 Water Pollution

Classified as WGK = 0 (self classification) (Wassergerahrdungsklasse in Germany). Not water endangering.

Section 13. Disposal Considerations

contaminated packaging should be disposed of in accordance with national and local regulations. Consult local authorities for advice. Incinerators should be fitted with acid scrubbing and run at a sufficient temperature to avoid evolution of dioxins.

Recycle if possible.

Section 14. Transport Information

Not classified as dangerous goods under transport regulations.

Section 15. Regulatory information

Not Applicable at this time

Section 16. Other information

Full list of precautionary phrases

P273 Avoid release to the environment.

P501 Dispose of contents and container in accordance with local regulation.

Wording of any hazard classes listed in section 3

- FL 3 Flammable liquid, category 3
- AH 1 Aspiration hazard, category 1
- **SCI 2** Skin corrosion/irritation, category 2
- **SS 1** Skin sensitisation, category 1
- **SS 1B** Skin sensitisation, category 1B
- EH A1 Aquatic hazard, acute, category 1
- EH C1 Aquatic hazard, chronic, category 1
- EH C2 Aquatic hazard, chronic, category 2

Wording of any hazard statements listed in section 3

- H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effect
- H411 Toxic to aquatic life with long lasting effects